



# **Aniseed Balls**

**CONTRACT CARPET TILES**

**Sweets**  
Collection  
By Flooring Industries

# Product description

## Aniseed Balls

- ◆ **Aniseed Balls** has a practical range of 36 vibrant colours, which are designed to coordinate with the modern office interior. This durable product is ideal for the corporate office user looking for practicality and durability. Aniseed Balls can either be laid broadloom or quarter turned achieving a remarkably high quality finish that is virtually seamless. Aniseed Balls is manufactured of a robust polyamide yarn that has good soil hiding qualities and is suitable for a wide range of commercial locations, both in the public and private sector.
- ◆ Aniseed Balls is a stock product be available for delivery throughout the United Kingdom, See our website @ [www.flooringindustries.co.uk](http://www.flooringindustries.co.uk)

### Usages

- ◆ Offices
- ◆ Schools
- ◆ Universities
- ◆ Public Buildings
- ◆ Hospital
- ◆ Nursing homes
- ◆ Industrial Units
- ◆ Banks

# Aniseed Balls



Coffee



Walnut



Mineralite



Suede Tan



Taupe



Marshwood



Metallic Onyx



Dove



Russian Sky



Raven Black



Graphite



Smokey Mount

# Aniseed Balls



**True Burgundy**



**Bronze**



**Desert Sun**



**Regal Red**



**Mountain Wood**



**Gold**



**Bay Blue**



**Regal Blue**



**Blue Ice**



**Deeper Navy**




**Slate Blue**



**Shadow Mist**

# Aniseed Balls



Sherwood



Grass



Mt. Olive Green



Willow



Spice Green



Golden Olive



Deep Waters



Hunter Green



English Blue



Grape



True Burgundy



Adobe

# Technical Specification

## Aniseed Balls Carpet Tiles

- ◆ 1st March 2006

### Warranty

- ◆ 10 years subject to Flooring Industries Conditions

### Construction

- ◆ 1/10 Gauge Loop, 100% Aquafil Altro6

### Total Weight.

- ◆ 4.35 kgs sq. mt. (Nom)

### Pile Weight.

- ◆ 530gms sq.mt. (Nom)

### Backing.

- ◆ Bitumen with Glass fibre

### Dimensions.

- ◆ Pile Height 2.7mm (Nom), Total Height 6.0mm (Nom), Tile size 50cm x 50cm(nom)

### Dimensional Stability.

- ◆ EN989. Max -0.2%

### Colour Fastness.

- ◆ EN ISO 105-B02/ x12/ E01, Light: 5 Water: 4-5 Rubbing: 4

### Flammability.

- ◆ NFP 92-506 M3: NBN S21-203 A3
- ◆ DIN 4102: B1 P-MPA-E-01-645

### Static.

- ◆ Permanently antistatic:PrEN 1815 <2KV
- ◆ Transversal resistance ISO/DIS 10965 <1010 Ohm

### Comfort.

- ◆ EN1307 Luxury rating LC1

## Usage.

- ◆ EN1307: 4 Heavy contract

## Castor Test.

- ◆ En1307 rating 2.8 Class A continuous use

## Acoustic.

- ◆ ISO 140-8 In 24db. ISO 354 request full results

## Thermal Resistance

- ◆ ISO 8302: Thermal Resistance 0.053 qm K/W Suitable for Underfloor Heating

## Environmental:

- ◆ Compatible production. GUT20640 Minimal odours and emissions, recycled waste.

## Installation

- ◆ Install to BS5325, CFA: best practice guide. Broadloom or Tessellated
- ◆ We reserve the right to improve and change the specification of the product without notification

# Aniseed Balls Installation Specification

**Aniseed Balls** 50x50cm x 6.0mm thick bitumen backed carpet tiles manufactured 100% Aquafil Altro6 Polyamide Yarn. Available in 36 standard colours delivered from stock.

## Preparation:

Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floorcoverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floorcoverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

## Surface Preparation

The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.

Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.

Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.

Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.

Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier.

## Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

## Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifier F41
- ◆ Sealer F70
- ◆ Screeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required

## Carpet Tiles

- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01923 211151 Fax no. 01923 818564

## Reference:

- ◆ Aniseed Balls
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ BS EN1307 LC3 Grade 3 Heavy Commercial
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 7.5 mm
- ◆ Colour Pattern:
- ◆ For complete technical literature or samples phone
- ◆ 01923 211151 or Email: [sales@flooringindustries.co.uk](mailto:sales@flooringindustries.co.uk)