

# Begonia Carpet Tiles

1<sup>st</sup> June 2008

## Warranty

10 years subject to Flooring Industries Conditions

## Construction

1/10<sup>th</sup> Gauge tufted loop Polyamide Antron

## Total Weight

4.95kgs sq. mt. (Nom)

## Pile Weight

800 grms sq.mt. (Nom)

## Backing

Bitumen with Glass fibre

## Dimensions

Pile Height 4.5mm (nom), Total Height 8.2mm (nom), Tile size 50cm x 50cm (nom)

## Dimensional Stability

N989. Max -0.2%

## Colour Fastness

EN ISO 105-B02/ x12/ E01, Light: 5, Water: 4-5, Rubbing: 4-5

## Flammability

NFP 92-506 M3

## Static.

Permanently antistatic:PrEN 1815 <2Kv

## Surface Resistance

BS ISO 10965: 1998 (2005) Vertical  $1.8 \cdot 10^9$  ohms. Horizontal  $1.8 \cdot 10^9$  ohms.

## Comfort.

EN1307 Luxury rating LC2

## Usage.

EN1307: 3 Commercial Use

## Castor Test.

En1307 rating 2.4 Class A continuous use

## Acoustic.

ISO 140-8 23db ISO 354 Request full results

## Thermal Resistance

BS4745: 2005 (5085-1:1089)Togs Mean: 0.63

## Environmentally

Compatible production Emissions, recycled waste. Compatible production. Minimal odours and waste

## Installation

Install to BS5325, CFA: best practice guide. Broadloom or Tessellated

We reserve the right to improve and change the specification of the product without notification