



Candy Twist

CONTRACT CARPET TILES

Sweets
Collection
By Flooring Industries

Product description

Candy Twist

- ◆ **Candy Twist** has a flexible colour pallet, which easily coordinates with any office interior. This durable cost effective carpet tile, offers a fresh pallet of practical yet modern colourways within a reasonable budget. Candy Twist can either be laid broadloom or quarter turned achieving a high quality finish. The product is manufactured out of a combination of polyamide for its durability and polyamide space dyed yarns for an attractive multicoloured appearance that effectively takes the eye away from the effects of dirt and soiling. Candy Twist is suitable for a wide range of commercial locations and is particular popular for use in office accommodation.
- ◆ Candy Twist is a standard stock product and readily available for delivery being supplied to a net work of dealers through out the United Kingdom, via our website @ www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Schools
- ◆ Universities
- ◆ Public Buildings
- ◆ Hospital
- ◆ Nursing homes
- ◆ Industrial Units
- ◆ Banks

Candy Twist



Mountain Wood



Marsh Wood



Harbor Tan



Smokey Mountain

Candy Twist



Mineralite



Lagoon Blue



Saxony Blue



Caramel

Candy Twist



Slate Blue



Shadow Mist



Adobe



Frozen Grape

Technical Specification

Candy Twist

- ◆ 1st March 2005
- ◆ Warranty
- ◆ 10 years subject to
- ◆ Flooring Industries Conditions
- ◆ Construction.
- ◆ 1/10 Gauge Loop
- ◆ 100% Solution Dyed Alto Croma
- ◆ Total Weight.
- ◆ 4.58 kgs sq.mt. (Nom)
- ◆ Pile Weight.
- ◆ 600gms sq.mt. (Nom)
- ◆ Backing.
- ◆ Bitumen with Glass fibre
- ◆ Dimensions.
- ◆ Pile Height 3.0 mm (Nom)
- ◆ Total Height 6.8 mm (Nom)
- ◆ Tile size 50cm x 50cm
- ◆ Dimensional Stability.
- ◆ EN989. Max -0.2%
- ◆ Colour Fastness.
- ◆ EN ISO 105-B02/ x12/ E01
- ◆ Light: 7 Water: 4-5 Rubbing: 4
- ◆ Flammability.
- ◆ NFP 92-506 M3: NBN S21-203 A3
- ◆ DIN 4102: B1 P-MPA-E-01-645
- ◆ Static.
- ◆ Permanently antistatic:
- ◆ PrEN 1815 <2KV
- ◆ Transversal resistance
- ◆ ISO/DIS 10965 <108 Ohm

Comfort.

- ◆ EN1307 Luxury rating LC1

Usage.

- ◆ EN1307: 3 Heavy contract

Castor Test.

- ◆ En1307 rating 3.2
- ◆ Class A continuous use

Acoustic.

- ◆ ISO 140-8 In 26 db.
- ◆ ISO 354 request full results

Thermal Resistance

- ◆ ISO 8302: Thermal Resistance 0.055 qm K/W
- ◆ Suitable for Underfloor Heating

Environmental:

- ◆ Compatible production.
- ◆ GUT20631 Minimal odours
- ◆ And emissions, recycled waste.

Installation

- ◆ Install to BS5325, CFA: best practice guide. Broadloom or Tessellated

Flooring Industries Ltd

- ◆ We reserve all rights for technical improvements.

Candy Twist Installation Specification

Product:

- ◆ **Candy Twist** Carpet Tile 50x50cm x 6.8mm thick bitumen backed carpet tile manufactured BCF Nylon-space dyed Yarn and is available in 12 standard colour ways

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floor coverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floor coverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.
- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifier F41
- ◆ Sealer F70
- ◆ Seeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required
- ◆ Carpet Tiles
- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01924 406161 Fax no. 01923 211151

Reference:

- ◆ Candy Twist
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ Heavy contract
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 6.8 mm
- ◆ Colour Pattern:
- ◆ For complete technical literature or samples phone
- ◆ **01923 211151** or Email: sales@flooringindustries.co.uk