



Granny Sookers

CONTRACT CARPET TILES

Sweets
Collection
By Flooring Industries

Product Description

Granny Sookers

- ◆ Granny Sookers is a practical range of 24 rich and vibrant colours, which are designed to coordinate with the modern office interior. This durable product is ideal for the corporate office user looking for practicality. Particularly when floorcoverings are being replaced when floor boxes are being repositioned and extensions, walls and cupboards are moved, thus requiring new carpet. Granny Sookers has great dye consistency between one batch and another. This along with superior colour retention Granny Sookers has better appearance consistency from one batch to another and therefore floors look better when replacement tile are laid. Granny Sookers can either be laid broadloom or quarter turned achieving a remarkably high quality finish that is virtually seamless. Granny Sookers is manufactured in a robust polyamide solution dyed yarn that is effective for its soil hiding properties and stain resistance. Granny Sookers is suitable for a wide range of commercial locations and is particular popular for use in office accommodation by corporate end users.

www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Schools
- ◆ Universities
- ◆ Public Buildings
- ◆ Hospital
- ◆ Nursing homes
- ◆ Industrial Units
- ◆ Banks


Granny Sookers



Black



Charcoal



Dark Grey



Woodland Bark



Mid Grey



Beige




Soft Grey



Natural Beige

Granny Sookers



Dark Brown



Red Plum



Bark



Red



Orange Brown



Red Black



Mustard



Purple Grey

Granny Sookers



Dark Blue



Green



Royal Blue



Green Beige



Bright Blue



Light Blue



Coral Blue



Fresh Blue

Technical Specification

Granny Sookers Tiles

1st March 2005

Warranty

- ◆ 10 years subject to Flooring Industries Conditions

Construction

- ◆ 1/10 Gauge Loop, 100% Solution Dyed Alto Cromo

Total Weight.

- ◆ 4.58 kgs sq. mt. (Nom)

Pile Weight.

- ◆ 600gms sq.mt. (Nom)

Backing.

- ◆ Bitumen with Glass fibre

Dimensions.

- ◆ Pile Height 3.0mm (Nom), Total Height 6.8mm (Nom), Tile size 50cm x 50cm (nom)

Dimensional Stability.

- ◆ EN989. Max -0.2%

Colour Fastness.

- ◆ EN ISO 105-B02/ x12/ E01, Light: 7 Water: 4-5 Rubbing: 4

Flammability.

- ◆ NFP 92-506 M3: NBN S21-203 A3
- ◆ DIN 4102: B1 P-MPA-E-01-645

Static.

- ◆ Permanently antistatic: PrEN 1815 <2KV
- ◆ Transversal resistance ISO/DIS 10965 <108 Ohm

Comfort.

- ◆ EN1307 Luxury rating LC1

Usage.

- ◆ EN1307: 3 Heavy contract

Castor Test.

- ◆ En1307 rating 3.2 Class A continuous use

Acoustic.

- ◆ ISO 140-8 In 26 db. ISO 354 request full results

Thermal Resistance

- ◆ ISO 8302: Thermal Resistance 0.055 qm K/W Suitable for Underfloor Heating

Environmental:

- ◆ Compatible production. GUT20631 Minimal odours and emissions, recycled waste.

Installation

- ◆ Install to BS5325, CFA: best practice guide. Broadloom or Tessellated
- ◆ We reserve the right to improve and change the specification of the product without notification

Granny Sookers Installation Specification

Product:

- ◆ **Granny Sookers** carpet tile 50x50cm x 6.8mm thick bitumen backed carpet tiles manufactured 100% Solution Dyed AltoChroma, and is available in 24 colours.

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floorcoverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floorcoverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.
- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifier F41
- ◆ Sealer F70
- ◆ Screeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required
- ◆ Carpet Tiles
- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01923 211151 Fax no. 01923 818564

Reference:

- ◆ Granny Sookers
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ BS EN1307 LC2 Grade 3 Heavy contact
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 6.8 mm
- ◆ Colour Pattern:
- ◆ T.B.A

For complete technical literature or samples phone
01923 211151 or Email: **sales@flooringindustries.co.uk**