



Liquorish Allsorts

CONTRACT CARPET TILES

Sweets
Collection

By Flooring Industries

Product description

Liquorish Allsorts

Liquorish Allsorts carpet tiles are of a Linear sculptured construction, manufactured in 9 plain and subtle shades of pastel, 6 modern multicoloured combinations, and 3 three very striking tonal contrasts in grey. These entire colour ways have there own characteristics and are very suitable for creating a striking office interior. The products are to be laid quarter turn creating a dramatic and stylish installation. The product is manufactured from Branded Polyamide yarns designed for durability and soil hiding characteristics, thus making them suitable heavy contract locations.

- ◆ Liquorish Allsorts is readily available and can be supplied through out the United Kingdom.
www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Schools
- ◆ Universities
- ◆ Public Buildings
- ◆ Retail shops, outlets

Liquorish Allsorts



2007599TTPERU



2007669TTPERU



2007249TTPERU

Liquorish Allsorts



2009599LINUP



2009948LINUP



2009265LINUP



2009931LINUP



2009659LINUP



2009189LINUP

Liquorish Allsorts



2007099PERU



2007369PERU



2007149PERU



2007631PERU



2007551PERU



2007826PERU



2007082PERU



2007193PERU



2007181PERU

Technical Specification

Liquorish Allsorts Carpet Tiles

- ◆ 1st June 2008

Warranty

- ◆ 10 years subject to Flooring Industries Conditions

Construction.

- ◆ 1/10th Gauge tufted loop Solution Dyed Polyamide

Total Weight.

- ◆ 4.6 kgs sq. mt. (Nom)

Pile Weight.

- ◆ 750 Gms per sq.mt. (Nom)

Backing.

- ◆ Bitumen with Glass fibre

Dimensions.

- ◆ Pile Height 3.0 mm (Nom),
- ◆ Total Height 7.2mm(Nom),
- ◆ Tile size 50cm x 50cm

Dimensional Stability.

- ◆ EN989. Max -0.2%

Colour Fastness.

- ◆ EN ISO 105-B02/ x12/ E01
- ◆ Light: 7 Water: 4-5, Rubbing: 4-5

Static.

- ◆ Permanently antistatic: PrEN 1815 <2Kv

Surface Resistance

- ◆ BS ISO/DIS 10965: 1998 (2005) 109ohms.

Flammability.

- ◆ EN 13501-1BF-S1 Less than 25mm flame spread on an incline burner. Maximum results achievable for a textile floorcoverings. "1" Best smoke emission result

Comfort.

- ◆ EN1307 Luxury rating LC2

Usage.

- ◆ EN1307: 4 Commercial Use

Castor Test.

- ◆ En1307 rating 2.8 Class "A" continuous use

Acoustic.

- ◆ ISO 140-8 23db, ISO 354 Request full results

Thermal Resistance

- ◆ ISO 8354 – 0,051qm K/W:0.079 qm K/W, Suitable for Underfloor Heating

Installation

- ◆ Install to BS5325, CFA: best practice guide. Tessellated Recommended

Liquorish Allsorts Installation Specification

Flooring Industries Installation Specification

Product:

- ◆ **Liquorish Allsorts** 50x50cm x 7.2mm thick bitumen backed carpet tiles manufactured 100% Polyamide. Available in 18 standard colour ways

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floorcoverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floorcoverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.

- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allow to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ **Tackifer** F41
- ◆ **Sealer** F70
- ◆ **Screeding** Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required

Carpet Tiles

- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01923 211151 Fax no. 01923 818564

Reference:

- ◆ Liquorish allsorts
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ BS EN1307 LC2 Grade 4 Heavy Contract
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 7.2 mm
- ◆ Colour Pattern:
- ◆ For complete technical literature or samples phone
- ◆ 01923 211151 or Email: sales@flooringindustries.co.uk