

Maestro 4000 Carpet Tiles

1st March 2005

Warranty

10 years subject to Flooring Industries Conditions

Construction

1/10 Gauge Loop BCF Nylon-space dyed Yarn

Total Weight.

4.4 kgs sq. mt. (Nom)

Pile Weight.

550gms sq.mt. (Nom)

Backing.

Bitumen with Glass fibre

Dimensions.

Pile Height 4.2 mm (Nom), Total Height 7.5 mm (Nom), Tile size 50cm x 50cm

Dimensional Stability.

EN989. Max -0.2%

Colour Fastness.

EN ISO 105-B02/ x12/ E01, Light: 5 Water: 4-5 Rubbing: 4

Flammability.

EN 13501-1BF-S1 Less than 25mm flame spread on an incline burner. Maximum results achievable for a textile floorcoverings. "1" Best smoke emission result

Static.

Permanently antistatic: Will not generate static at 20 deg C and 30% RH

Comfort.

Reduces impact noise and fatigue

Usage.

EN1307: Heavy contract

Castor Test.

En1307 rating 2.9 Class A continuous use

Thermal Resistance

Suitable for under floor heating

Environmental:

Continually working on more environmentally friendly methods of manufacture

Installation

Install to BS5325, CFA: best practice guide. Broadloom or Tessellated

We reserve the right to improve and change the specification of the product without notification