

Resort Carpet Tiles

1st March 2005

Warranty

10 years subject to Flooring Industries Conditions

Construction

1/10 Gauge Loop, 100% Solution Dyed Alto Croma

Total Weight.

4.58 kgs sq. mt. (Nom)

Pile Weight.

600gms sq.mt. (Nom)

Backing.

Bitumen with Glass fibre

Dimensions.

Pile Height 3.0mm (Nom), Total Height 6.8mm (Nom), Tile size 50cm x 50cm(nom)

Dimensional Stability.

EN989. Max -0.2%

Colour Fastness.

EN ISO 105-B02/ x12/ E01, Light: 7 Water: 4-5 Rubbing: 4

Flammability.

NFP 92-506 M3: NBN S21-203 A3

DIN 4102: B1 P-MPA-E-01-645

Static.

Permanently antistatic:PrEN 1815 <2KV

Transversal resistance ISO/DIS 10965 <10⁸ Ohm

Comfort.

EN1307 Luxury rating LC1

Usage.

EN1307: 3 Heavy contract

Castor Test.

En1307 rating 3.2 Class A continuous use

Acoustic.

ISO 140-8 In 26 db. ISO 354 request full results

Thermal Resistance

ISO 8302: Thermal Resistance 0.055 qm K/W Suitable for Underfloor Heating

Environmental:

Compatible production. GUT20631 Minimal odours and emissions, recycled waste.

Installation

Install to BS5325, CFA: best practice guide. Broadloom or Tessellated

We reserve the right to improve and change the specification of the product without notification