



Thumb Drops

CONTRACT CARPET TILES

Sweets
Collection
By Flooring Industries

product description

Thumb Drops

- ◆ **Thumb Drops** is a practical loop pile carpet tile that gives a quality finish in a beautiful low lustre yarn. A range of 18 practical colours, are available, which ideally suit the modern office interior.
- ◆ Thumb Drops has an extremely flexible dyeing procedure meaning that Flooring Industries can dye to order thus personalising any cooperate interior. Thumb Drops can be either laid in one direction or quarter turned.
- ◆ Thumb Drops is manufactured from the well-respected Antron yarn with its excellent soil hiding properties, and resistance to abrasion thus assuring that carpets continue to look good when properly maintained.
- ◆ Thumb Drops is suitable for a wide range of commercial locations and is particular popular for use in office accommodation by corporate end users for its flexibility and performance.
- ◆ Thumb Drops is a standard stock product and readily available for delivery being supplied to a net work of dealers through out the United Kingdom, via our website @ www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Public Buildings
- ◆ Banks

Thumb Drops



Dark Red



Dark Blue



Turquoise/Grey



Red



Mid Blue



Light Blue/Grey



Red/Blue



Purple/Blue



Light Grey

Thumb Drops



Dark Grey



Dark Green



Dark Red/Brown



Mid Grey



Mid Green



Mid Orange/Brown



Light Grey/Brown



Mid Green/Grey



Mid Red/Brown

Thumb Drops



Dark Red / Brown



Mid Orange / Brown

Technical Specification

Thumb Drops

- ◆ 1st March 2005
- ◆ Warranty
- ◆ 10 years subject to Flooring Industries Conditions
- ◆ Construction.
- ◆ 1/10 Gauge Loop 100% Antron XL
- ◆ Total Weight.
- ◆ 4.85 kgs sq. mt. (Nom)
- ◆ Pile Weight.
- ◆ 580gms sq.mt. (Nom)
- ◆ Backing.
- ◆ Bitumen with Glass fibre and non woven fleece.
- ◆ Primary backing man made
- ◆ Dimensions.
- ◆ Pile Height 4.0 mm (Nom)
- ◆ Total Height 7.5 mm (Nom)
- ◆ Tile size 50cm x 50cm
- ◆ Dimensional Stability.
- ◆ EN989. Max -0.2%
- ◆ Colour Fastness.
- ◆ EN ISO 105-B02/ x12/ E01 Light:
- ◆ 5 Water: 4-5 Rubbing: 4
- ◆ Flammability.
- ◆ NFP 92-506 M3: NBN S21-203 A3 DIN 4102:
- ◆ B1 P-MPA-E-01-645
- ◆ Static.
- ◆ Antistatic: PrEN 1815 <2KV
- ◆ Transversal resistance ISO/DIS 10965 <1010 Ohm
- ◆ Comfort.
- ◆ EN1307 Luxury rating LC1
- ◆ Usage.
- ◆ EN1307: 3 Heavy Contract

Castor Test.

- ◆ En1307 rating 2.9
- ◆ Class A continuous use

Acoustic.

- ◆ ISO 140-8 29 db. ISO 354 request full results

Thermal Resistance

- ◆ ISO 8302: Thermal Resistance 0.057 gm K/W
- ◆ Suitable for Under-floor Heating

Environmental Compatible Production.

- ◆ GUT20631 Minimal odours and emissions,
- ◆ recycled waste.

Installation

- ◆ Install to BS5325, CFA: best practice guide.
- ◆ Broadloom or Tessellated
- ◆ We reserve all rights for technical improvements.

Thumb Drops

Installation Specification

Product:

- ◆ **Thumb Drops** 50x50cm x 7.5mm thick bitumen backed carpet tiles manufactured 100% Antron XL, and available in 18 standard colours from stock.

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floorcoverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floorcoverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.
- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifier F41
- ◆ Sealer F70
- ◆ Seeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required
- ◆ Carpet Tiles
- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01924 211151 Fax no. 01923 818564

Reference:

- ◆ Thumb Drops
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ BS EN1307 LC1 Grade 3 Heavy contact
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 7.5 mm
- ◆ Colour Pattern:
- ◆ T.B.A
- ◆ For complete technical literature or samples phone
- ◆ 01923 211151 or Email: sales@flooringindustries.co.uk
- ◆ www.flooringindustries.co.uk