



Tosca Rosa

CONTRACT CARPET TILES

By Flooring Industries

Product description

Tosca Rosa

- ◆ Tosca Rosa carpet tiles are a durable low cost loop pile carpet tile, which offers practical colours and texture at a budget. Tosca Rosa can either be laid broadloom or quarter turned, having a high quality finish. The product is manufactured out of durable polypropylene with a good reputation for robustness and resistance to staining. Tosca Rosa is suitable for a wide range of commercial locations.
- ◆ Tosca Rosa is a standard stock product and readily available for delivery, being supplied to a net work of dealers through out the United Kingdom, via our website @

www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Schools
- ◆ Universities
- ◆ Public Buildings
- ◆ Hospital
- ◆ Nursing homes
- ◆ Industrial Units
- ◆ Speculative developments

Tosca Rosa



Black magic



Absolutely



Banshee



Shadow Dancer



South Seas



Malton



Pascali



Azure Sea



Mango Tango



Ice Crystal



Burgund



Garden Party

Tosca Rosa



Technical Specification

Tosca Rosa Carpet Tiles

01 April 2008

Warranty

- ◆ 10 years subject to Flooring Industries Conditions

Construction

- ◆ 1/10th Gauge Tufted Cut Loop

Fibre Type

- ◆ Solution Dyed Polypropylene

Total weight

- ◆ 4.6kgs sq. mt. (Nom)

Pile Weight

- ◆ 550 g/m² (Nom)

Backing

- ◆ Bitumen with glass fibre

Dimensions

- ◆ Pile height 3.5mm(nom), Total height 6.5mm(nom), Tile size 50cm x 50 cm(nom)

Dimensional Stability

- ◆ ISO 2551Pass

Flammability

- ◆ EN 14041: 2004 EN ISO 9239-1 Cfls1

Static

- ◆ Permanently antistatic, Stroll Test PrEN 1815 <2K

Usage

- ◆ Commercial Usage

Castor Test

- ◆ EN1307 Occasional Usage

Thermal retention

- ◆ Suitable for Underfloor heating

Environmental

- ◆ Continually working on more environmentally friendly methods of manufacture

Installation

- ◆ Install to BS5325, CFA: best practice guide. Broadloom or Tessellated

- ◆ We reserve the right to improve and change the specification of the product without notification

Tosca Rosa Standard Installation Specification

Product:

- ◆ **Tosca Rosa** carpet tiles 50x50cm x 6.5mm thick bitumen backed carpet tiles manufactured 100% Polypropylene, and are available in 13 standard colour ways

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floorcoverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floorcoverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.
- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifer F41
- ◆ Sealer F70
- ◆ Seeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors
- ◆ Carpet Tiles
- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01923 211151 Fax no. 01923 818564

Reference:

- ◆ Tosca Rosa
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ Commercial Usage
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 6.5 mm
- ◆ Colour Pattern:
- ◆ For complete technical literature or samples phone
- ◆ **01923 211151** or Email: sales@flooringindustries.co.uk
- ◆ WWW.flooringindustries.co.uk