



Yellow Bellies

CONTRACT CARPET TILES

Sweets
Collection
By Flooring Industries

Product description

Yellow Bellies

- ◆ **Yellow Bellies** carpet tiles are of a tufted cut pile carpet construction with a subtle pin dot design, the product offers affordable luxury making it a popular choice in areas such as hospitality retail and office accommodation. The range features 18 attractive colourways designed to bring a touch of class to any interior. Yellow bellies can be either lay quarter turn or in the same direction, which achieves an outstanding broadloom, finish. Yellow Bellies is manufactured from Du Pont Antron XL with its proven reputation for durability and good soil hiding properties, and design gives the product excellent resistance to wear making it an ideal choice for a wide range of commercial locations.
- ◆ Yellow Bellies is a standard stock product and readily available for delivery being supplied to a net work of dealers through out the United Kingdom, via our website @ www.flooringindustries.co.uk

Usages

- ◆ Offices
- ◆ Retail
- ◆ Hospitality
- ◆ Student accommodation
- ◆ Public Buildings
- ◆ Shops and outlets

Yellow Bellies



Deeper Navy



Raven Black



Grape



Blue Lagoon



Graphite



Frozen Grape



Slate Blue



Grey Marshwood



Gray Metal

Yellow Bellies



Coffee



True Burgundy



Forrest Green



Mountain Wood



Adobe



English Ivy



Camel



Bronze



Sherwood

Yellow Bellies



Royal Blue



Rainbow Drops

Technical Specification

Yellow Bellies

- ◆ 1st March 2005

Construction.

- ◆ 1/10 Gauge Cut plain velour
- ◆ Solution dyed AltoCroma

Total Weight.

- ◆ 4.8 kgs sq. mt. (Nom)

Pile Weight.

- ◆ 750gms sq.mt. (Nom)

Backing.

- ◆ Bitumen with Glass fibre

Dimensions.

- ◆ Pile Height 3.5 mm (Nom)
- ◆ Total Height 7.1 mm (Nom)
- ◆ Tile size 50cm x 50cm

Dimensional Stability.

- ◆ EN989. Max -0.2%

Colour Fastness.

- ◆ EN ISO 105-B02/ x12/ E01
- ◆ Light: 5 Water: 4-5 Rubbing: 4-5

Flammability.

- ◆ NFP 92-506 M3: NBN S21-203 A3
- ◆ DIN 4102: B1 P-MPA-E-02-566Static.

Permanently antistatic:

- ◆ PrEN 1815 <2Kv

Surface Resistance:

- ◆ ISO/ DIS 10965 1010 ohms.

Comfort.

- ◆ EN1307 Luxury rating LC2

Usage.

- ◆ EN1307: 3 Heavy contract

Castor Test.

- ◆ En1307 rating 2.9
- ◆ Class A continuous use

Acoustic.

- ◆ ISO 140-8 25db
- ◆ ISO 354 Request full results

Environmental:

- ◆ Compatible production.
- ◆ GUT210003 Minimal odours
- ◆ And emissions, recycled waste.

Installation

- ◆ Install to BS5325, CFA: best practice guide. Broadloom or Tessellated
- ◆ We reserve all rights for technical improvements.

Yellow Bellies Installation Specification

Product:

- ◆ **Yellow Bellies** 50x50cm x 7.1.0mm thick bitumen backed carpet tiles manufactured 100% DU Pont Antron XL. Available in 18 standard colour ways

Preparation:

- ◆ Installation should be carried out in accordance with the recommendations detailed in British Standard Code of Practice for Installation of Textile Floor coverings BS 5325: 1983 (or any revision of this standard). It is also recommended that the installation should be in accordance with The Contract Flooring Association Manual for Installation of Textile Floor coverings (October 1989). If surface tackifiers or other adhesives are to be used, the adhesive manufacturer's guidelines with reference to the Control of Substances Hazardous to Health (COSHH) Regulations and Section 6 of the Health and Safety at Work Act 1974 (as amended by the Consumer Protection Act 1987) should be consulted. Before commencing to lay tiles check that they are from the same batch number, which is stamped on the back of each tile. It is important that batches are not mixed as shades may vary from batch to batch.

Surface Preparation

- ◆ The floor should be clean, level, dry and free from any contaminants such as oil, grease and polish. A new concrete slab should have moisture content, when measured with a hygrometer, less than 75% relative humidity.
- ◆ Dusty floors and surfaces that are very absorbent should be swept clean and the surface sealed with an approved sealer. The sealer should be allowed to dry before the application of any tackifier or adhesive system.
- ◆ Concrete screeds should be sound and any damaged areas or holes should be made good using an approved screeding material.
- ◆ Vinyl tiles should be firmly adhered to the floor and all surface treatments should be removed prior to the application of the tackifier.
- ◆ Floorboards should be level and firmly fixed. Uneven surfaces should be levelled by the application of hardboard or plywood, and the latter may require sealing to prevent the absorption of applied tackifier

Application of surface tackifier

- ◆ In all Installations it is recommended that an all-over surface tackifier method should be used. We recommend an anti-slip surface tackifier such as F.Ball Styccobond F41 applied using a roller and tray. This method ensures that the correct amount of adhesive is applied and avoids over-application, which may cause problems with raised floor panels and timber floors. Never pour surface tackifier directly from the drum onto a raised flooring system. The tackifier must be allowed to dry to clear tacky film in accordance with the manufacturers instructions. Under no circumstances must the tiles be laid in wet tackifier.

Recommended Materials

- ◆ Flooring Industries Ltd recommends the following materials: -
- ◆ Tackifier F41
- ◆ Sealer F70
- ◆ Seeding Stopgap Powder/Liquid system as appropriate
- ◆ Surface cleaner Styccoclean
- ◆ Fabricated underlay:
- ◆ See Flooring Industries Installation guide Surface Preparation timber Floors only if required
- ◆ Carpet Tiles
- ◆ Tufted carpet tiles Bitumen backing with glass fibre non-woven fleece
- ◆ Carpet Manufacture and reference:
- ◆ Flooring Industries Ltd P.O Box 290 Watford Hertfordshire Wd24 7LA Telephone no. 01923 211151 Fax no. 01923 818564

Reference:

- ◆ Yellow Bellies
- ◆ Type:
- ◆ Type N carpet tiles
- ◆ Classification:
- ◆ Heavy contract
- ◆ Width:
- ◆ 50x 50 cm
- ◆ Height:
- ◆ 6.8 mm
- ◆ Colour Pattern:
- ◆ For complete technical literature or samples phone
- ◆ **01923 211151** or Email: **sales@flooringindustries.co.uk**